


Tipo N PFA Isolato Doppio Coppia Termocoppia / Filo (IEC)




10m



TYPE-N

25M



TYPE-N

Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Tipo N PFA Isolato Doppio Coppia Termocoppia / Filo (IEC)

Doppia coppia intrecciata in Teflon PFA per estendere o realizzare semplici termocoppie. Il PFA Teflonha una buona resistenza e flessibilit meccanica, resistente a oli, acidi e altri fluidi nocivi, gas, vapore e pressione.

Specifiche
Specifications

General Description	Resistant to oils, acids other adverse agents and fluids. Good mechanical strength and flexibility. PTFE better for steam/elevated pressure environments.
Cable Length	10m, 25m, 50m, 100m, 200m
Cable Type	Single pair of PFA insulated conductors twisted together
Core / Strands	1/0.2mm
Conductor Cross Section 1/0.2 (mm²)	0.032
+ Colour	Pink
- Colour	White
Drain Wire	No
Insulation Material	PFA Teflon®
Loop Resistance 1/0.2 (Ohms per combined metre)	44.2
Max. Temperature	+260°C
Min. Temperature	-75°C
+ Conductor	Nicosil
- Conductor	Nisil



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Screen	No
Standards Met	Colour code (cores & jacket) to IEC-584-3
Thermocouple Type	N
Tolerance	Class 1