Termocoppia IEC Minerale Isolata con Potenziometro Filetato e 100mm di piombo IEC Twin Twisted Isolato con PFA - Tipo K - 1,0mm x 150mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

Hai bisogno di calibrare il sensore di temperatura?

Tracciabile secondo standard di calibrazione ISO17025 (UKAS), Labfacility offre la scelta tra una calibrazione tracciabile a 3 o 5 punti utilizzando la nostra struttura di calibrazione interna.

Tieni presente che se aggiungi un'opzione di calibrazione al tuo ordine verrai contattato per informazioni sulla consegna.

Specifiche

Specifications

Product Code	XE-3305-001
General Description	Mineral insulated thermocouple in various lengths terminated with 100mm, PFA insulated twin twisted IEC.
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	1.0mm
Probe Length	150mm
Sheath Material	310 Stainless Steel
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted IEC
Core / Strands	7/0.2mm
Termination Type	Bare Tails

Max. Temperature	750°C
Min. Temperature	-40°C
Standards Met	IEC 584
Series	Mineral Insulated