



**LABFACILITY**  
TEMPERATURE & PROCESS TECHNOLOGY

## **Termocoppia a isolamento minerale di stile industriale con testa terminale KNE - Tipo K - 6,0 mm di diametro - 200 mm di lunghezza**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

**Hai bisogno di calibrare il tuo sensore di temperatura?**

Tracciabile secondo gli standard di calibrazione ISO17025 (UKAS), Labfacility offre la possibilità di scegliere tra una calibrazione tracciabile a 3 o 5 punti utilizzando la nostra funzione di calibrazione interna, possibile selezionare qualsiasi punto di temperatura tra -10°C e +200°C.

**Tieni presente che se aggiungi un'opzione di calibrazione al tuo ordine, verrai contattato per informazioni sulla consegna.**

**Indicazioni****Specifications**

|                              |                                                                                    |
|------------------------------|------------------------------------------------------------------------------------|
| <b>Product Code</b>          | XE-3252-001                                                                        |
| <b>General Description</b>   | Highly flexible, sheath can be bent/formed to suit many applications and processes |
| <b>Sensor Type</b>           | Mineral insulated Thermocouple fitted with KNE terminal head                       |
| <b>Thermocouple Type</b>     | K                                                                                  |
| <b>Thermocouple Junction</b> | Insulated hot junction                                                             |
| <b>Probe Diameter</b>        | 6.0mm                                                                              |
| <b>Probe Length</b>          | 200mm                                                                              |
| <b>Sheath Material</b>       | 310 stainless steel sheath                                                         |
| <b>Head Type</b>             | KNE, Cast aluminium finish, screw type lid with chain                              |
| <b>Gland</b>                 | M16 x 1.5mm Plated brass gland fitted                                              |
| <b>Max. Temperature</b>      | 1100°C                                                                             |
| <b>Min. Temperature</b>      | -40°C                                                                              |
| <b>IP Rating</b>             | IP67                                                                               |