Sonda di drenaggio per autoclave Pt100 a resistenza al platino RTD / PRT a 4 fili

Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

Pt100 Sonda di temperatura per scarico autoclave e sterilizzatore

Da utilizzare per monitorare la temperatura del fluido nello scarico di uscita dello sterilizzatore

Specificamente progettato in conformit con HTM2010 Clausola 6.20 per fornire la migliore precisione possibile e

stabilit nell'ambiente rigoroso della camera di sterilizzazione

Compatibile con le pi comuni marche di autoclavi

Hai bisogno di calibrare il tuo sensore di temperatura?

Tracciabile secondo gli standard di calibrazione ISO17025 (UKAS), Labfacility offre la possibilit di scegliere tra una calibrazione tracciabile a 3 o 5 punti utilizzando la nostra funzione di calibrazione interna, possibile selezionare qualsiasi punto di temperatura tra -10C e +200C.

Tieni presente che se aggiungi un'opzione di calibrazione al tuo ordine, verrai contattato per informazioni sulla consegna.

Specifications

Product Code	XE-9512-001
General Description	Specifically designed in accordance with HTM2010 Clause 6.20 to provide the best possible accuracy and stability in the rigorous environment of the steriliser chamber.
Sensor Type	Pt100 (100 Ohms @ 0°C) to IEC 751: 2008, Class B, 4 wire connection
Probe Diameter	6mm
Probe Length	150mm
Sheath Material	316 stainless steel sheath below potting collar (9.5mm dia. x 44mm long)
Cable Length	1m
Cable Type	Teflon® insulated with braided screen
Core / Strands	7/0.2mm

Cable Termination	Bare Tails
Max. Temperature	+200°C
Min. Temperature	-50°C
Accuracy	Class B to IEC 751: 2008