



LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Termocoppia a isolamento minerale con testa terminale compatta KNS - Tipo K - Diametro 6,0 mm - Lunghezza 200 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Hai bisogno di calibrare il tuo sensore di temperatura?

Tracciabile secondo gli standard di calibrazione ISO17025 (UKAS), Labfacility offre la possibilità di scegliere tra una calibrazione tracciabile a 3 o 5 punti utilizzando la nostra funzione di calibrazione interna, possibile selezionare qualsiasi punto di temperatura tra -10°C e +200°C.

Tieni presente che se aggiungi un'opzione di calibrazione al tuo ordine, verrai contattato per informazioni sulla consegna.

Indicazioni**Specifications**

Product Code	XE-3322-001
General Description	Flexible mineral insulated probe with 310 stainless steel sheath
Sensor Type	Type 'K' (Nickel Chromium/Nickel Aluminium) to IEC 584
Thermocouple Junction	Insulated hot junction
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	6.0mm
Probe Length	200mm
Sheath Material	310 stainless steel sheath
Head Type	KNS, Cast aluminium finish, screw type lid with chain. Head fitted 2-way ceramic block
Gland	M16 x 1.5mm Plated brass gland fitted
Max. Temperature	+1100°C (Max temp of head is 170°C)
Min. Temperature	-40°C
IP Rating	IP67



Series

Mineral Insulated