Kit da corsa economico 2 con sonda regolabile per pneumatici







Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

Kit da corsa economico 2

Include sonda regolabile per pneumatici da corsa, misuratore digitale e valigia morbida

Sonda Pneumatici

Questa sonda per pneumatici da corsa a risposta molto rapida ha una regolazione manuale della profondit da 1 mm a 15 mm

Un intervallo di temperatura da -50 a +250C

Tipo di giunzione: Messa a terra

Un tempo di risposta inferiore a 0,5 secondi

Dotato di caviglio a spirale da 1 m e piccolo tappo

Pu essere usato con qualsiasi termometro digitale K con una presa di ingresso mini

GM1312 Termometro Digitale Generale (K,J,T,E,N,R/S)

Modalit K, J, T, E, N, R/S.

2 modalit di temperatura: C, F e

Un pulsante per passare anche tra la modalit F/ C e alternare tra MAX/MIN/MG

2 canali di temperatura: T1 / T2

Misurazione differenziale della temperatura

Allarme di sovraccarico se l'input supera il range di misura selezionato

Viene fornito con fondina in gomma che protegge il misuratore dagli impatti. Design portatile e compatto

Specifications

Product Code	XE-KITRACE2
General Description	Includes adjustable racing tyre probe, digital meter and soft carry case
Sensor Type	Adjustable tyre probe, grounded junction
Thermocouple Type	Type K, This very fast response racing tyre probe has a manual depth adjustment from 1 mm to 15 mm
Probe Diameter	1.1mm
Probe Length	1mm up to 15mm

Cable Length	1m
Cable Type	Coiled lead
Cable Termination	Miniature plug
Max. Temperature	+250°C
Min. Temperature	-50°C
Digital Thermometer	GM1312 General Purpose Digital Thermometer *K, J, T, E, N, R/S modes. *2 temperature modes: ° C, ° F *One push button to switch between ° F/° C mode as well to switch between MAX/MIN/AVG *2 temperature channels: T1 / T2 *Differential temperature measurement *Overload display alert if input exceeds the selected measurement range *Comes with rubber holster that protects the meter from impact Portable and compact design