

Termometro digitale Digitron 2029T (Tipi K, T, J, N, R, S) con sonde opzionali



[Click here to view product](#)

Product Code	XE-3992-BUNDLE
General Description	Provides precise, stable readings and high accuracy even in the harshest of environments. Unit is simple to operate, fast, reliable and built to last. In this unique range we can offer advanced features such as speed read, logging and dual input instruments
Accuracy	0.1% rdg $\pm 0.2^{\circ}\text{C}/0.4^{\circ}\text{F}$ above $?100^{\circ}\text{C}/? 148^{\circ}\text{F}$ 0.5% rdg $\pm 0.2^{\circ}\text{C}/0.4^{\circ}\text{F}$ below
Connector Type	Connector Type: 2 pin mini
Dimensions	155 x 67 x 40mm/6.1 x 2.6 x 1.6?
Max. Temperature	50°C (122°F)
Min. Temperature	-10°C (14°F)

Weight	180g / 6.4oz
Power Consumption	Battery Life: Typically 500 hours. Low Battery Check: Symbol appears on display
Power Supply	Two AA or equivalent cells (not supplied)
Standards Met	Environmental Specifications: IP65 (IP67 optional)
Thermocouple Type	Sensor Type: K,T, J, N, R/S
Resolution of data display	0.1° from ?199.9°C to +199.9°C/?199.9°F to +392.0°F 1°C elsewhere