

Termocoppia a risposta rapida da 0,75 mm di diametro con spina IEC miniaturizzata - Giunzione isolata - 250 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Tipo K Acciaio inox 316 a isolamento minerale, dotato di miniplug

Se hai bisogno di quantit maggiori, invia un'e-mail sales@labfacility.com o telefona alla nostra linea di vendita 01243 871280.

Hai bisogno di calibrare il tuo sensore di temperatura?

Tracciabile secondo gli standard di calibrazione ISO17025 (UKAS), Labfacility offre la possibilit di scegliere tra una calibrazione tracciabile a 3 o 5 punti utilizzando la nostra funzione di calibrazione interna, possibile selezionare qualsiasi punto di temperatura tra -10C e +200C.

Tieni presente che se aggiungi un'opzione di calibrazione al tuo ordine, verrai contattato per informazioni sulla consegna.

Indicazioni

Specifications

Product Code	XE-0199-001
General Description	Type K 316 stainless steel, Fitted with miniplug
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath
Probe Diameter	0.75mm
Probe Length	250mm
Sheath Material	316 stainless steel
Termination Type	Thermocouple IEC Mini plug (Max Temp 200°C)
Max. Temperature	+750°C
Min. Temperature	-100°C
Tolerance	Class 1
Standards Met	In accordance with IEC 584