



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Termocoppia a risposta rapida diametro 0,75 mm con code nude IEC - Giunzione con messa a terra - 250 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Sonde a termocoppia con giunto di transizione a diametro fine

Le giunzioni delle termocoppie sono disponibili con messa a terra, per un tempo di risposta pi rapido e un costo inferiore; o isolato, per l'isolamento elettrico della termocoppia dalla guaina.

Se hai bisogno di quantit maggiori, invia un'e-mail sales@labfacility.com o telefona alla nostra linea di vendita 01243 871280.

Hai bisogno di calibrare il tuo sensore di temperatura?

Tracciabile secondo gli standard di calibrazione ISO17025 (UKAS), Labfacility offre la possibilit di scegliere tra una calibrazione tracciabile a 3 o 5 punti utilizzando la nostra funzione di calibrazione interna, possibile selezionare qualsiasi punto di temperatura tra -10C e +200C.

Tieni presente che se aggiungi un'opzione di calibrazione al tuo ordine, verrai contattato per informazioni sulla consegna.

Indicazioni

Specifications

Product Code	XE-0193-001
General Description	Industrial use Infrared Thermometer
Sensor Type	Mineral Insulated
Thermocouple Type	K
Battery	2 x 1.5 volt LR44 coin cell (included)
Element/hot junction	Single element, junction grounded from sheath
Display	6mm LCD
Probe Diameter	0.75mm
Probe Length	250mm
Sheath Material	K - Stainless steel 316
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (Max Temp 200°C)

Cable Length	100mm
Cable Type	PFA insulated twin twisted IEC (Temp -75 to +250°C)
Core / Strands	7/0.2mm
Termination Type	Fortfix sealed with = +VE leg 15mm long and -VE leg 10mm long
Resolution	0.1°C (switchable)
Max. Temperature	+650°C
Min. Temperature	-40°C
Tolerance	Class 1
Standards Met	In accordance with IEC 584
Accuracy	+/-2°C
Dimensions	18 x 90 mm
Weight	20 grams
Important Information	Please Note: these are industrial IR thermometers, so please check the specifications before purchasing as a restocking fee of 20% will apply to unused products.