Termocoppia minerale isolata con diametro 0,81 mm e spina ANSI in miniatura giunzione messa a terra - lunghezza sonda 250 mm

Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

Tipo K con spina ANSI in miniatura in acciaio inox 316

Se hai bisogno di quantit maggiori, ti preghiamo di inviare sales@labfacility.com email o di telefonare alla nostra linea vendita 01243 871280.

Hai bisogno di calibrare il sensore di temperatura?

Tracciabile secondo standard di calibrazione ISO17025 (UKAS), Labfacility offre la scelta tra una calibrazione tracciabile a 3 o 5 punti utilizzando la nostra struttura di calibrazione interna.

Tieni presente che se aggiungi un'opzione di calibrazione al tuo ordine verrai contattato per informazioni sulla consegna.

Indicazioni

Specifications

Product Code	XE-0253-001
General Description	Highly flexible, sheath can be bent/formed to suit many applications and processes
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction grounded from sheath
Probe Diameter	0.81mm
Probe Length	250mm
Sheath Material	K - Stainless steel 316
Pot Type	Plain (+200°C)
Cable Length	1M
Cable Type	PFA Teflon® insulated flat pair cable and tails (colour coded to ANSI MC96.1) (Max Temp 250°C)
Core / Strands	7/0.2mm

Termination Type	Miniature flat pin plug, colour coded In accordance with ANSI MC96.1
Max. Temperature	+650°C. Plug Max. temperature range: 200°C
Min. Temperature	-40°C
Tolerance	Class 1
Standards Met	ANSI MC96.1
Connector Type	Plug
Connection Type	Miniature
Colour	Yellow