



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Sonda Pt100 a doppio elemento a isolamento minerale con cavo di prolunga - diametro 6,0 mm - lunghezza 150 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

PRT duplex a isolamento minerale con due rivelatori PT100 indipendenti all'interno della punta della sonda. Ci consente di collegare una sonda a due dispositivi di misurazione o controllo; In alternativa, un sensore pu essere utilizzato come primario e l'altro come backup, eliminando la necessit di rimuovere e sostituire la sonda in caso di guasto di uno dei sensori.

Sonda Pt100 per alte temperature, robusta e flessibile con doppio elemento

Adatto per molte applicazioni industriali, tra cui alta pressione, vuoto e vibrazioni

Pt100 Classe B, collegamento 2 x 3 fili

Guaina flessibile in acciaio inox, diametro 6,0 mm

La sonda pu essere piegata per consentire il montaggio in posizioni scomode

1 metro 6 conduttori isolato in teflon, piombo schermato

Temperatura nominale del sensore da -50 C a +500 C

Indicazioni

Specifications

Product Code	XE-3695-001
General Description	Flexible mineral insulated probe, 316 stainless steel sheath
Sensor Type	Pt100 (100 Ohms @ 0°C) to IEC 751, Class B, 2 x 3 wire
Probe Diameter	6.0mm
Probe Length	150mm
Termination Type	2 x 3 wire tails – allows connection to any 2 or 3 wire PT100 instrument