


Tipo T PFA Flat Pair Thermocouple / Wire IEC - Trebello 1/0,508mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Cavo/filo termocoppia a coppia piatta isolata con PFA - Posato piatto, affiancato e rivestito in PFA. Classe di tolleranza 1

Non riesci a trovare quello che ti serve? Chiama o invia una email al nostro team di vendita tecnica al +44 (0) 1243 871 280 o sales@labfacility.com per assistenza nella selezione dei prodotti e nel supporto tecnico

Specifiche

Specifications

General Description	Resistant to oils, acids other adverse agents and fluids. Good mechanical strength and flexibility. PTFE better for steam/elevated pressure environments.
Cable Length	10m, 25m, 50m, 100m, 200m
Cable Type	PFA insulated, laid flat with PFA jacket
Core / Strands	1/0.508mm
Conductor Cross Section 1/0.508 (mm²)	0.203
Outer Colour	Brown
+ Colour	Brown
- Colour	White
Drain Wire	No
Insulation Material	PFA Insulated
Loop Resistance 1/0.508 (Ohms per combined metre)	2.5
Max. Temperature	260°C
Min. Temperature	-75°C
+ Conductor	Copper



- Conductor	Constantan
Screen	No
Standards Met	Colour code (cores & jacket) to IEC-584-3
Thermocouple Type	T
Tolerance	Class 1