


Tipo K PTFE Tipo Coppia Termocoppia Intrecciata Isolata / Filo (IEC) - Trebello 1/0,315mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Tipo K con cavi / filo termocoppia a doppia coppia intrecciata (IEC)

Doppia coppia intrecciata isolante in PTFE. Il PTFE ha una buona resistenza e flessibilit  meccanica, resistente a oli, acidi e altri fluidi avversi.

Specifiche

Specifications

General Description	Resistant to oils, acids adverse agents and fluids. Good mechanical strength and flexibility.
Cable Length	10m, 25m, 50m, 100m, 200m
Cable Type	Twin twisted pair for extending or making simple thermocouples
Core / Strands	1/0.315mm
Conductor Cross Section 1/0.315 (mm²)	0.078
+ Colour	Green
- Colour	White
Drain Wire	No
Insulation Material	PTFE insulated
Loop Resistance 1/0.315 (Ohms per combined metre)	12.8
Max. Temperature	260°C
Min. Temperature	-75°C
+ Conductor	Nickel Chromium
- Conductor	Nickel Aluminium
Screen	No



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Standards Met	Colour code (cores & jacket) to IEC-584-3
Thermocouple Type	K
Tolerance	Class 1